

# Drinking Water Filter Cartridges



## **D-10: Taste and Odor/Chlorine/Sediment**

Replaces AMETEK/Kleen-Plus model C-1 filter cartridge

- Chlorine, bad taste and odor reduction
- 5-micron (nominal) filtration
- Activated carbon-impregnated cellulose
- Filter life of up to 3 months or 250 gallons



The D-10 is Tested and Certified by NSF International to ANSI/NSF Standard 42 for the reduction of Taste and Odor, Chlorine Class I, Particulate Class II.



## **D-20: Taste and Odor/Chlorine**

Replaces AMETEK/Kleen-Plus model CC-10 filter cartridge

- Chlorine, bad taste and odor reduction
- Granular activated carbon
- High surface area for maximum adsorption
- Filter life of up to 12 months or 1000 gallons



The D-20 is Tested and Certified by NSF International to ANSI/NSF Standard 42 for the reduction of Taste and Odor, Chlorine Class I.



## **D-30: Cryptosporidium and Giardia Cysts/Asbestos/Chlorine/Bad Taste and Odor/Sediment**

Replaces AMETEK/Kleen-Plus model CBC-10 filter cartridge

- >99.95% removal of disease-causing *Giardia* and *Cryptosporidium* cysts
- Asbestos, chlorine, bad taste and odor, and sediment reduction
- 0.5 micron filtration (nominal)
- CBC® activated carbon block
- Filter life of up to 12 months or 1000 gallons



The D-30 is Tested and Certified by NSF International to ANSI/NSF Standard 42-Taste and Odor, Chlorine Class I, Particulate Class I. Standard 53 - Cyst, Asbestos and Turbidity Reduction.



## **D-40: Lead/Mercury/Lindane and Atrazine/Cryptosporidium and Giardia Cysts/Asbestos/Chlorine/Bad Taste and Odor/Sediment**

Replaces AMETEK/Kleen-Plus model CMR-10R filter cartridge

- Lindane and Atrazine (a pesticide and herbicide), lead, and mercury reduction
- >99.95% removal of disease-causing *Cryptosporidium* and *Giardia* cysts
- Asbestos, chlorine, bad taste and odor, and sediment reduction
- 0.5-micron filtration (nominal)
- CBC® activated carbon block with lead-reduction media
- Filter life up to 6 months or 600 gallons



The D-40 is Tested and Certified by NSF International to ANSI/NSF Standard 42 for the reduction of Taste and Odor, Chlorine Class I, Particulate Class I. Standard 53 - Lead, Lindane, Atrazine, Mercury, Cyst, Asbestos and Turbidity Reduction.



**Universal Slim Design!  
Provides better,  
fresher-tasting water for  
drinking and cooking**

Fits Culligan/AMETEK models  
US-600, US-550, US-560, CTR-210,  
SY-2000, and SY-5167







Tested and Certified by NSF International.

**Culligan**  
is Water

**NOTE: Contaminants or other substances removed or reduced by this water treatment device are not necessarily in your water. Percentages may vary with local water conditions.**

# Drinking Water Filter Cartridges

Drinking Water Filter Cartridge Selection Guide				
				
Reduces:	D-10	D-20	D-30	D-40†
sediment	X	X	X	X
bad taste and odor	X	X	X	X
chlorine	X	X	X	X
<i>Giardia</i> and <i>Cryptosporidium</i> cysts			X	X
asbestos			X	X
Lindane and Atrazine (a pesticide and herbicide)				X
lead and mercury				X
Filter life**	3 months 250 gal.	12 months 1000 gal.	12 months 1000 gal.	6 months 600 gal.

\*\* Filter cartridge life varies depending on usage and water conditions.

† Contains built-in flow control at 0.6 gpm. For use with separate faucet in under-sink installations.

Individual Unit				
MODEL#	PART#	WEIGHT (lbs.)	DIMENSIONS (in.) L x W x H	UPC 0-51678
D-10	155528-26	0.94	9.75 x 4.8 x 2.4	00272-8
D-20	155532-27	1.01	9.75 x 2.4 x 2.4	15571-4
D-30	155465-27	1.17	9.75 x 2.4 x 2.4	16271-2
D-40	155466-27	1.75	9.75 x 2.4 x 2.4	40371-6

Case						
MODEL#	PART#	CASE PACK	CASE WT.(lbs.)	CASE cu. ft.	CASE DIMENSIONS (in.) L x W x H	CASE UPC 1-00-51678
D-10	155528-26	12 pr.	11.3	1.18	17.25 x 11.5 x 10.25	00272-5
D-20	155532-27	12	12.1	0.74	12.75 x 9.63 x 10.25	15571-1
D-30	155465-27	12	14	0.74	12.75 x 9.63 x 10.25	16271-9
D-40	155466-27	4	7	0.25	5.19 x 5.19 x 10.63	40371-3

Cut-Case						
MODEL#	PART#	CASE PACK	CASE WT.(lbs.)	CASE cu. ft.	CASE DIMENSIONS (in.) L x W x H	CASE UPC 5-00-51678
D-10-D	155528-98	16 pr.	15.1	1.63	22.5 x 11.6 x 10.8	00272-3
D-20-D	155532-98	12	12.1	0.52	10.81 x 10.3 x 8.1	15571-9
D-30-D	155465-98	12	14	0.52	10.81 x 10.3 x 8.1	16271-7
D-40-D	155466-98	9	15.8	0.52	10.81 x 10.3 x 8.1	40371-1

**WARNING:** Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

**NOTE:** Contaminants or other substances removed or reduced by this water treatment device are not necessarily in your water. Filter must be maintained according to manufacturer's instructions, including replacement of filter cartridges.

**Customer Service:**  
**1-800-634-1455**  
 M-F 7:30 a.m – 5:00 p.m. CST

**Culligan**  
 502 Indiana Avenue • P.O. Box 1047  
 Sheboygan, WI 53082-1047 U.S.A.  
 FAX: (920) 457-6652  
<http://www.culligan.com>  
 International calls: (920) 451-9322  
 International e-mail:  
[international@plymouthwater.com](mailto:international@plymouthwater.com)